TOP ALTITUDE: ASSIGNED BY ATC

TAKEOFF MINIMUMS

Rwy 8R: FLOGS and NOCHI Transitions standard with minimum climb of 500′ per NM to 6000. GREBE and SLNNK Transitions standard with minimum climb of 500′ per NM to 13500.

Rwy 22: FLOGS and NOCHI Transitions standard with minimum climb of 515′ per NM to 7200. GREBE and SLNNK Transitions standard with minimum climb of 515′ per NM to 13500.

Rwy 26L: FLOGS and NOCHI Transitions standard with minimum climb of 570′ per NM to 6800. GREBE and SLNNK Transitions standard with minimum climb of 570′ per NM to 13500.



D-ATIS
120.0 254.3
CLNC DEL
125.0 379.1
GND CON
121.9 348.6
EL PASO TOWER
118.3 239.275
EL PASO DEP CON
119.15 263.0
ALBUQUERQUE CENTER
128.2 285.5

(NARRATIVE ON FOLLOWING PAGE)

NOTE: Takeoff Rwy 8R, do not exceed 220K until passing JAPOD.
NOTE: Takeoff Rwy 26L, do not exceed 220K until passing 4462.
NOTE: For use by Turbojet aircraft only.
NOTE: RADAR required for non-GPS equipped aircraft.
NOTE: DME/DME/IRU or GPS required.
NOTE: RNAV 1.