

WAAS
CH **42612**
W16A

APP CRS
164°

Rwy Ldg **7502**
TDZE **710**
Apt Elev **710**

RNAV (GPS) RWY 16
FORT WORTH MEACHAM INTL (FTW)

⚠

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -16°C (4°F) or above 47°C (116°F). DME/DME RNP-0.3 NA.

⚠

** RVR 1800 authorized with use of FD or AP or HUD to DA.

MALSR

MISSED APPROACH: Climb to 3000 direct PAXXE and hold.

ATIS 120.7	LONE STAR APP CON 118.1 306.95 (N) 135.975 379.9 (S)	MEACHAM TOWER 118.3 257.8	GND CON 121.9
----------------------	--	-------------------------------------	-------------------------

Procedure NA for arrivals on UKW VORTAC via V17-161 northbound.

Key features on the chart include:

- UKW VORTAC** at 3000 ft, 144° bearing, 3.5 NM distance.
- FOXEB IAF** at 3000 ft, 074° bearing, 5 NM distance.
- WORD IAF** at 2500 ft, 164° bearing, 6 NM distance.
- MESDE FAF** at 990 ft, 974° bearing, 4 NM distance.
- RW16** at 710 ft elevation.
- MISSED APCH FIX** at 3000 ft, 164° bearing, 4 NM distance.
- GP 3.00° TCH 57** for the final approach.

ELEV 710

D

TDZE 710

Key features on the chart include:

- GP 3.00° TCH 57** for the final approach.
- Altitudes** of 91, 7502, 150, 35, and 34 ft.
- Distances** of 1.5, 0.5, 0.75, and 0.5 NM.

HIRL Rwy 16-34
MIRL Rwy 17-35

4 NM Holding Pattern

WOROD

3000

344°

164°

GP 3.00° TCH 57

MESDE

2500

1.5 NM to RW16

*LNAV only.

RW16

CATEGORY	A	B	C	D
LPV DA **	910/24	200 (200-½)		
LNAV/VNAV DA	1284-1½	574 (600-1½)		
LNAV MDA	1240/24	530 (600-½)	1240/50 530 (600-1)	1240/60 530 (600-1¼)
CIRCLING	1260-1 550 (600-1)	1280-1 570 (600-1)	1340-1¾ 630 (700-1¾)	1500-2½ 790 (800-2½)

FORT WORTH, TEXAS
Amdt 1C 19MAY22

32°49'N-97°22'W

FORT WORTH MEACHAM INTL (FTW)
RNAV (GPS) RWY 16