

WAAS CH 90320 W19A	APP CRS 192°	Rwy Ldg TDZE 754 Apt Elev 757	6526 754 757
--	------------------------	---	---

RNAV (GPS) Z RWY 19

KANSAS CITY DOWNTOWN/WHEELER FLD (MKC)

RNP APCH-GPS.

▼

Rwy 19 helicopter visibility reduction below RVR 4000 NA.
Inop table does not apply to LPV* all Cats. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -19°C or above 54°C. For inop ALS, increase LPV visibility all Cats to RVR 5500.

MAJSA

⚡

⚡


⚡

MISSED APPROACH: Climb to 1300 then climbing right turn to 4000 direct MIFEV and on track 236° to YETUK and hold.

*Missed approach requires minimum climb of 300 feet per NM to 1500.

#Missed approach requires minimum climb of 360 feet per NM to 2400.

ATIS 120.75	KANSAS CITY APP CON 118.4 307.35	DOWNTOWN TOWER 133.3 233.7	GND CON 121.9
-----------------------	--	--------------------------------------	-------------------------



MISSED APCH FIX

MIFEV

YETUK

1300

4000

tr 236°

YETUK

4 NM

236°

296°

(not to scale)

COVRI

4 NM Holding Pattern

012°

6000

3000

192°

2600

GP 3.00°

TCH 46

5.7 NM

7.1 NM

CATEGORY	A	B	C	D
LPV DA*		1004/40	250 (300-¾)	
LPV DA		1097/40	343 (400-¾)	
LNAV/VNAV DA#		1077/40	323 (400-¾)	
LNAV/VNAV DA		1468-1¾	714 (800-1¾)	

ELEV 757

D

TDZE 754

192°

61

4

1

5550 X 100

4827 X 150

TWR

RLS Rwy 1

REIL Rws 1 and 22

HIRL Rws 4-22 and 1-19