

LOC/DME I-CFN	APP CRS	Rwy Ldg	25R 11134	25L 11095
<u>111.1</u>	251°	TDZE	104	104
Chan 48		Apt Elev	128	128

ILS or LOC RWY 25R
LOS ANGELES INTL (LAX)

From CRCUS, SEAVU, TRNDO, CLPUR: RNAV 1-GPS required.
DME or RADAR required.

T Simultaneous approach authorized. Simultaneous approach authorized with HHR. For inop ALS increase Sidestep 25L Cat C visibility to 1½ SM. #RVR 1800 authorized with use of FD or AP or HUD to DA.

MALSI
Rwy 25

ALSF-2
Rwy 25L

MISSED APPROACH: Climb to 2000 on heading 251° until crossing SMO R-160 then left turn on heading 236° and SMO VOR/DME R-195 to CATLY INT/SMO 15.7 DME and hold.

	SOCAL APP CON				LOS ANGELES TOWER		GND CON	
D-ATIS	124.3	363.2 (APCH from W)	124.9	269.0 (090°-224°)	133.9	239.3 (N)	121.65	327.0 (N)
133.8	124.5	235.975 (225°-044°)	128.5	360.7 (045°-089°)	120.95	379.1 (S)	121.75	327.0 (S)
							121.4	327.0 (W)

