

VORTAC MRB

112.1

Chan 58

APP CRS

290°

Rwy Ldg TDZE

N/A

Apt Elev

565

EASTERN WV RGNL/SHEPHERD FLD (MRB)


VOR-A

RADAR required for procedure entry at HARPP.

When local altimeter setting not received, use HGR altimeter setting: increase all MDAs 80 feet and Circling visibility Cats C/D ¼ SM.

MISSED APPROACH: Climbing left turn to 3000 direct MRB VORTAC and hold, continue climb in hold to 3000.

ASOS 119.925	POTOMAC APP CON 126.825 239.025	MARTINSBURG TOWER★ 124.3 (CTAF) 233.7	GND CON 121.8 257.65	UNICOM 122.95
-----------------	------------------------------------	--	-------------------------	------------------



3000

MRB

MRB VORTAC

One Minute Holding Pattern

110°

6000

3000

290°

5.7 NM

CATEGORY	A	B	C	D	E
CIRCLING	1120-1 555 (600-1)	1240-1 675 (700-1)	1240-2 675 (700-2)	1320-2½ 755 (800-2½)	2180-3 1615 (1700-3)

FAF to MAP 5.7 NM

Knots	60	90	120	150	180
Min:Sec	5:42	3:48	2:51	2:17	1:54