



WAAS CH 93823 W23A	APP CRS 227°	Rwy Ldg TDZE Apt Elev	8700 50 54
--	------------------------	-----------------------------	---------------------------------------

RNAV (GPS) Y RWY 23

RHODE ISLAND TF GREEN INTL (PVD)

RNP APCH - GPS.		MALSR	MISSED APPROACH: Climb to 1700 then climbing right turn to 2500 direct FOSTY and hold.
For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -16°C or above 54°C. Inop ALS, increase LNAV Cats C/D visibility to RVR 6000. *RVR 1800 authorized with use of FD or AP or HUD to DA.			
D-ATIS 124.2	PROVIDENCE APP CON ★ 123.675 244.875	PROVIDENCE TOWER ★ 120.7 (CTAF) 0 257.8	GND CON 121.9 348.6



1700		2500	FOSTY	VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 41).
RW23		WIVPA 1.6 NM to RW23 600	CUSKA 1900	FEDED 2300
1.6 NM		4.1 NM	6.8 NM	GP 3.00° TCH 51
CATEGORY	A	B	C	D
LPV DA *	250/24		200 (200-½)	
LNAV/VNAV DA	355/24		305 (400-½)	
LNAV MDA	460/24	410 (500-½)	460/40	410 (500-¾)
CIRCLING	560-1 506 (600-1)	640-1 586 (600-1)	640-1½ 586 (600-1½)	860-2½ 806 (900-2½)

NE-1, 25 DEC 2025 to 22 JAN 2026

NE-1, 25 DEC 2025 to 22 JAN 2026