

SNIDR TWO DEPARTURE (RNAV)

**TOP ALTITUDE:
ASSIGNED BY ATC**

RNAV 1 - DME/DME/IRU or GPS.

RADAR required for non-GPS equipped aircraft. RADAR required.

TAKEOFF MINIMUMS

Rwy 10: Standard with minimum climb of 230'/NM to 1900.

Rwy 14: Standard with minimum climb of 220'/NM to 1900.

Rwy 28: 300-1% or standard with minimum climb of 230'/NM to 900, or alternatively, with standard takeoff minimums and a normal 200'/NM climb gradient, takeoff must occur no later than 1800' prior to DER.



Rwy 32: Standard with minimum climb of 230'/NM to 1700.

SAN ANTONIO DEP CON
125.7 290.225

CLNC DEL (When twr closed)

121.7

GND CON
121.7 379.9
STINSON TOWER ★
118.2 379.9



NOTE: Chart not to scale.

DEPARTURE ROUTE DESCRIPTION

TAKEOFF RUNWAY 10: Climb on heading 100° or as assigned by ATC, for vectors to WRKIT, hence. . .
 TAKEOFF RUNWAY 14: Climb on heading 142° or as assigned by ATC, for vectors to WRKIT, hence. . .
 TAKEOFF RUNWAY 28: Climb on heading 280° or as assigned by ATC, for vectors to WRKIT, hence. . .
 TAKEOFF RUNWAY 32: Climb on heading 322° or as assigned by ATC, for vectors to WRKIT, hence. . .

... on track 080° to CHURN, then on track 085° to SNIDR. Expect filed altitude 10 minutes after departure.

BLUMS TRANSITION (SNIDR2.BLUMS)
CAAGE TRANSITION (SNIDR2.CAAGE)
FFSH TRANSITION (SNIDR2.FFSH)
MOLL TRANSITION (SNIDR2.MOLL)
SEEDS TRANSITION (SNIDR2.SEEDS)
WEMAR TRANSITION (SNIDR2.WEMAR)
WHAEL TRANSITION (SNIDR2.WHAEL)
WYLSN TRANSITION (SNIDR2.WYLSN)

SNIDR TWO DEPARTURE (RNAV)

(SNIDR2.SNIDR) 07AUG25

SAN ANTONIO, TEXAS
STINSON MUNI (SSF)