

WAAS
CH **99502**
W20A

APP CRS
196°

Rwy Ldg
TDZE **54**
Apt Elev **56**

RNAV (GPS) Y RWY 20R

JOHN WAYNE/ORANGE COUNTY (SNA)

RNP APCH - GPS. RADAR required.

⚠

⚠

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below 5°C or above 54°C. Circling Rwy 20L NA at night. For inop ALS increase LNAV/VNAV visibility to 1 3⁄8 SM.
*RVR 1800 authorized with use of FD or AP or HUD to DA.

MALSR

MISSED APPROACH: Climb to 3000 direct MINOE.

D-ATIS 126.0	SOCAL APP CON 121.3 263.1	JOHN WAYNE TOWER ★ 126.8 (CTAF) 0 343.625	GND CON 120.8	UNICOM 122.95
------------------------	-------------------------------------	---	-------------------------	-------------------------

ELEV 56	D	TDZE 54
REIL Rwy 20L MIRL Rwy 2R-20L HIRL Rwy 2L-20R		
3000 MINOE VGSi and RNAV glidepath not coincident (VGSi Angle 3.00/TCH 68).		
CATEGORY	A	B
LPV DA*	255/24	201 (200-1/2)
LNAV/VNAV DA	516/50	462 (500-1)
LNAV MDA	580/24 526 (600-1/2)	580/55 526 (600-1)
CIRCLING	640-1 584 (600-1)	840-2 784 (800-2 1/4) 1180-3 1124 (1200-3)

SANTA ANA, CALIFORNIA

JOHN WAYNE/ORANGE COUNTY (SNA)

Amtd 4 26DEC24

33°41'N-117°52'W

RNAV (GPS) Y RWY 20R