

WAAS CH 58122 W22A	APP CRS 220°	Rwy Ldg TDZE Apt Elev	7001 378 378
--	------------------------	-----------------------------	---


RNAV (GPS) RWY 22

SCHENECTADY COUNTY (SCH)

NA Circling Rwy 10 NA at night. Baro-VNAV NA when using Albany altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C (5°F) or above 54°C (130°F). DME/DME RNP-0.3 NA. Helicopter visibility reduction below ¾ SM NA. VDP NA with Albany altimeter setting. When local altimeter setting not received, use Albany altimeter setting and increase LPV DA to 661, LNAV/VNAV DA to 749, and all MDA 40 feet, increase LPV and LNAV/VNAV all Cats, LNAV Cat C and D and Circling Cat C visibility ½ mile.

MISSED APPROACH:
Climb to 3700 direct
FOSRA and hold.

AWOS-3 119.275	ALBANY APP CON 132.825 263.075	SCHENECTADY TOWER ★ 121.3 (CTAF) 321.1	GND CON 121.9	UNICOM 122.95
--------------------------	--	---	-------------------------	-------------------------



		3700	FOSRA	
		* LNAV only.	* 1.5 NM to RW22	
		RW22	ZILVO	MULXI
		2200	2200	3000
		1.5 NM	4.1 NM	6.1 NM
CATEGORY	A	B	C	D
LPV DA		628-¾	250 (300-¾)	
LNAV/VNAV DA		716-1⅞	338 (400-1⅞)	
LNAV MDA	900-1	522 (600-1)	900-1½	522 (600-1½)
CIRCLING	900-1 522 (600-1)	940-1 562 (600-1)	1120-2¼ 742 (800-2¼)	1320-3 942 (1000-3)

