

WAAS CH 93504 W18A	APP CRS 180°	Rwy Ldg 10000 TDZE 641 Apt Elev 678
--	------------------------	--

RNAV (GPS) RWY 18L

TULSA INTL (TUL)

RNP APCH - GPS.

⚠


ASR


Circling NA for Cat E south of Rwy 8-26. Use of FD or AP required during simultaneous operations. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -11°C or above 54°C. For inop ALS, increase LPV Cat E visibility to RVR 4000, LNAV/VNAV all Cats visibility to RVR 5500, and LNAV Cat E visibility to 1¼ SM. Simultaneous approach authorized. LNAV procedure NA during simultaneous operations.

MALS R

MISSED APPROACH:
Climb to 3500 direct
ICECE and hold.

D-ATIS 124.9 377.2	TULSA APP CON 124.0 338.3	TULSA TOWER 121.2 310.8 (08/26, 18L/36R) 118.7 257.8 (18R/36L)	GND CON 121.9 348.6
------------------------------	-------------------------------------	--	-------------------------------



3500 ↑	ICECE 	VGSI and RNAV glidepath not coincident (VGSI Angle 2.75/TCH 56).				4 NM Holding Pattern	
							
CATEGORY	A	B	C	D	E		
LPV DA	841/24		200 (200-½)				
LNAV/VNAV DA	983/30		342 (400-⅔)				
LNAV MDA	1080/24	439 (500-½)	1080/40		439 (500-¾)		
CIRCLING	1120-1 442 (500-1)	1160-1 482 (500-1)	1500-2½ 822 (900-2½)	1520-2¾ 842 (900-2¾)	1520-3 842 (900-3)		

