

APP CRS	Rwy Ldg	7604
274°	TDZE	1068
	Apt Elev	1099

RNAV (RNP) Z RWY 27

YAKIMA AIR TRML/MCALLISTER FLD (YKM)


For uncompensated Baro-VNAV systems, procedure NA below -17°C (2°F) or above 54°C (130°F). RF required. Missed approach all Cats to RVR 4500 and RNP 0.30 DA visibility all Cats to 1 1/2 SM. DATVE transition NA when R-6714 A, C, D active.



MALSRS



MISSED APPROACH: Climb to 5100 on track 274° to YEPCU left turn to JOPDI left turn to ZEMUN left turn to MUDLE and hold.
* Missed approach requires a minimum climb of 215 feet per NM to 4300.

ATIS	SPOKANE APP CON *	YAKIMA TOWER *	GND CON	UNICOM
125.25	123.8 263.15	133.25 (CTAF) 0 257.8	121.9	122.95



 MIRL Rwy 4-22 HIRL Rwy 9-27 REIL Rws 4, 9, and 22	5100 ↑ tr 274° YEPCU JOPDI ZEMUN MUDLE OAKSS 2900						
	See planview for multiple IF locations.						
							
	CATEGORY	A		B		C	D
	RNP 0.10 DA*	1348/24 280 (300-½)					
RNP 0.30 DA	1468/45 400 (400-⅞)						
AUTHORIZATION REQUIRED							