

WAAS CH 90512 W27A	APP CRS 274°	Rwy Ldg TDZE Apt Elev 7604 1068 1099
--	------------------------	--

RNAV (GPS) X RWY 27

YAKIMA AIR TRML/MCALLISTER FLD (YKM)

RNP APCH.

▼

Circling NA south of Rws 9 and 27.

▲

For inop ALS, increase LPV all Cats visibility to 1¾ SM.

*

RVR 1800 authorized with use of FD or AP or HUD to DA.


MALSR

A5

MISSSED APPROACH:

Climb to 2100 then climbing right turn to 7000 direct GEBTE and hold. Continue climb-in-hold to 7000. *Missed approach requires minimum climb of 300 feet per NM to 3700. #Missed approach requires minimum climb of 300 feet per NM to 4900.

ATIS 125.25	SPOKANE APP CON * 123.8 263.15	YAKIMA TOWER * 133.25 (CTAF) 0 257.8	GND CON 121.9	UNICOM 122.95
-----------------------	--	--	-------------------------	-------------------------



ELEV 1099	D	TDZE 1068
-----------	----------	-----------

2100

7000

GEBTE

*LNAV only

*0.9 NM to RW27

AGITY

3.4 NM to RW27

RACOB

2900

ZUDAX

2900

OPISE

5 NM Holding Pattern

094°

6000

274°

4700

GP 3.00°

TCH 57

CATEGORY	A	B	C	D
LPV DA*	1268/24 200 (200-½)			
LPV DA	1668-1¼ 600 (600-1¼)			
LNAV MDA#	1400/24	332 (400-½)	1400/26	332 (400-½)
LNAV MDA	1720/24	652 (700-½)	1720-1¾	652 (700-1¾)
CIRCLING	1720-1	621 (700-1)	1880-2¼ 781 (800-2¼)	2280-3 1181 (1200-3)

MIRL Rwy 4-22

HIRL Rwy 9-27

REIL Rws 4, 9, and 22