



APCH CRS 355°	Rwy Idg TDZE Arpt Elev	9001 1361 1382	AL-482 (USAF)	ALTUS AFB (KLTS)
RNP APCH. DME/DME RNP-0.3 NA			ALSF-1	MISSED APPROACH: Climb to 4000 direct JEPKI and hold.
* When ALS inop increase RVR to 40, vis to 3/4 mile. ** When ALS inop increase CAT AB RVR to 55, vis to 1 mile; CAT CDE RVR 50, vis to 1 mile.				

ATIS★	FORT WORTH CENTER	APP CON	TOWER★	GND CON	CLNC DEL
109.8 273.5	133.5 350.35	125.1 353.7	119.65 254.4	121.85 275.8	120.65 284.7

*** Circling NA W of Rwy 36L-18R.

For uncompensated Baro-VNAV systems, procedure NA below -17°C (2°F) or above 54°C (130°F).



EMERG SAFE ALT 100 NM 4900

4000	JEPKI	VGSI and RNAV glidepath not coincident.	CIPNO	175°	3100	ELEV 1382	TDZE 1361
CATEGORY	A	B	C	D	E		
LNAV/VNAV DA*	1611/24		250	(300-½)			
LNAV MDA**	1700/24	339 (400-½)	1700/26	339	(400-½)		
CIRCLING***	1780-1 398 (400-1)	1840-1 458 (500-1)	1880-1½ 498 (500-1½)	2080-2¼ 698 (700-2¼)	2180-2¾ 798 (800-2¾)		