

WAAS CH 72905 W04A	APP CRS 039°	Rwy Ldg TDZE 5000 2885 Apt Elev 2885
--	------------------------	--

RNAV (GPS) RWY 4

LIBERAL MID-AMERICA RGNL (L.B.L.)


RNP APCH - GPS.

⚠

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -20°C or above 54°C. Circling NA east of Rwy 17-35. When local altimeter setting not received, use GUY altimeter setting and increase LPV DA to 3248 feet; increase LNAV/VNAV DA to 3412 feet and all visibilities ¾ SM. Increase all MDAs 120 feet and LNAV visibility Cat C/D ¾ SM, and Circling visibility Cat C/D ¼ SM. Baro-VNAV and VDP NA when using GUY altimeter setting.

MISSED APPROACH: Climb to 4800 direct NULEE and hold.

AWOS-3PT 118.375	KANSAS CITY CENTER 134.0 257.625	UNICOM 122.8 (CTAF)
----------------------------	--	-------------------------------



5 NM Holding Pattern		PERDE	LENDE	4800	NULEE
4800		219°	039°	4600	1.5 NM to RW04
GP 3.00°					RW04
TCH 39					
		6.2 NM	3.7 NM	1.5 NM	
CATEGORY	A	B	C	D	
LPV DA	3136-1		251 (300-1)		
LNAV/VNAV DA	3300-1 ¾		415 (500-1 ¾)		
LNAV MDA	3400-1 515 (600-1)		3400-1 ¾ 515 (600-1 ¾)		
CIRCLING	3400-1 515 (600-1)		3400-1 ½ 515 (600-1 ½) 3640-2 ½ 755 (800-2 ½)		

