

WAAS CH 86232 W13A	APP CRS 126°	Rwy Ldg 5601 TDZE 593 Apt Elev 595
--	------------------------	---

RNAV (GPS) RWY 13
SAN MARCOS RGNL (HYI)

RNP APCH-GPS.

⚠

Circling NA for Cat E southwest of Rwy 13-31. Inop table does not apply to LPV all Cats.
For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -16°C or above 54°C.
For inop ALS, increase LNAV/VNAV Cat E visibility to 1 SM and LNAV Cat E visibility to 1½ SM.

MALS

MISSED APPROACH:

Climb to 3000 direct HODAL and hold.

ATIS 120.825	AUSTIN APP CON 119.0 370.85	SAN MARCOS TOWER★ 126.825 (CTAF) 0	GND CON 120.125
------------------------	---------------------------------------	---	---------------------------

ELEV 595

TDZE 593

6 NM Holding Pattern

ORALE

JISGO

YOYTU

RW13

GP 3.00°

TCH 57

CATEGORY	A	B	C	D	E
LPV DA	793-¾ 200 (200-¾)				
LNAV/VNAV DA	946-¾ 353 (400-¾)				
LNAV MDA	1120-¾ 527 (600-¾)	1120-1¼ 527 (600-1¼)			
CIRCLING	1120-1 525 (600-1)	1240-1¾ 645 (700-1¾)	1320-2¼ 725 (800-2¼)	1340-2¾ 745 (800-2¾)	

3000 HODAL

126°

521.4 X 100

26

35

5

0.4% UP

TWR

MIRL Rwy 8-26, 13-31, and 17-35 **0**

AUSTIN, TEXAS
Amdt 2C 12AUG21

29°54'N-97°52'W

SAN MARCOS RGNL (HYI)
RNAV (GPS) RWY 13

SC-3, 25 DEC 2025 to 22 JAN 2026

SC-3, 25 DEC 2025 to 22 JAN 2026