


WAAS CH 90432 W31A	APP CRS 306°	Rwy Ldg TDZE Apt Elev	5601 583 595
--	------------------------	-----------------------------	---

RNAV (GPS) RWY 31
SAN MARCOS RGNL (HYI)



T Baro-VNAV NA when using New Braunfels altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -16°C (3°F) or above 54°C (130°F). When local altimeter setting not received, use New Braunfels altimeter setting and increase all DA 43 feet and all MDA 60 feet; increase LPV all Cats and LNAV/VNAV all Cats visibility 1/8 mile, and LNAV Cat C/D/E and Circling Cat C/D visibility 1/4. Circling NA for Cat E SW of Rwy 13-31. DME/DME RNP-0.3 NA. VDP NA with New Braunfels altimeter setting. Helicopter visibility reduction below 3/4 SM NA.

MISSED APPROACH:
Climb to 3500 direct
ORALE and hold.

ATIS 120.825	AUSTIN APP CON 119.0 370.85	SAN MARCOS TOWER ★ 126.825 (CTAF) 0	GND CON 120.125
------------------------	---------------------------------------	--	---------------------------



ELEV 595		TDZE 583
----------	--	----------



CATEGORY		A	B	C	D	E
LPV	DA	860-7/8 277 (300-7/8)				
RNAV/ RNAV	DA	906-1 323 (400-1)				
RNAV	MDA	980-1 397 (400-1)		980-1 1/8 397 (400-1 1/8)		
CIRCLING		1080-1 485 (500-1)	1120-1 525 (600-1)	1240-1 3/4 645 (700-1 3/4)	1320-2 1/4 725 (800-2 1/4)	1340-2 3/4 745 (800-2 3/4)

AUSTIN, TEXAS
Orig-B 23JUN16

29°54'N-97°52'W

SAN MARCOS RGNL (HYI)
RNAV (GPS) RWY 31

SC-3, 25 DEC 2025 to 22 JAN 2026