

ILS or LOC RWY 4

LOC I-GLO 108.5	APCH CRS 038°	Rwy Idg 10,001 TDZE 4284 Arprt Elev 4295	[USAF]
---------------------------	-------------------------	---	--------

CANNON AFB (KCVS)

ATC RADAR or DME required. Missed approach requires use of RNAV or ATC RADAR monitoring.

*When ALS inop, increase all CAT RVR to 40 and vis to ¾ miles.

ATIS 119.1 269.9	APP CON 118.425 352.1	TOWER 120.4 270.25	GND CON 121.9 275.8
		CLNC DEL 120.2 293.225	

**When ALS inop, increase CAT AB RVR to 55 and vis to 1 mile, CAT CDE RVR to 60 and vis to 1½ miles.

Localizer unuseable 26° right of course.

EMERG SAFE ALT 100 NM 9000

ZILEM CVS 12 6000 GS 2.50° TCH 46	VGS1 TCH 41' and the procedure TCH 46' is greater than 3'. CUVGO CVS 5.7 5700 038°
---	---

CATEGORY	A	B	C	D	E
S-ILS 4 *	4484/24		200	(200-½)	
S-LOC 4 **	4680/24	396 (400-½)	4680/35	396 (400-¾)	
CIRCLING	4840-1	545 (600-1)	4860-1½	5000-2¼	5020-2½
			565 (600-1½)	705 (800-2¼)	725 (800-2½)

ELEV 4295	TDZE 4284
-----------	-----------

HIRL all rwys

FAF to MAP 5.2 NM					
Knots	60	90	120	150	180
Min:Sec	5:12	3:28	2:36	2:05	1:44