

WAAS CH 99732 W10A	APP CRS 101°	Rwy Ldg TDZE 38 Apt Elev 40	8005
--	------------------------	---	-------------



RNAV (GPS) RWY 10

Wallops Flight Facility (WAL)

DME/DME RNP -0.3 NA. Rwy 10 helicopter visibility reduction below ¾ SM NA. When local altimeter setting not received, use Salisbury altimeter setting and increase all DA 60 feet and all visibilities ¼ SM. Increase all MDA 60 feet and all Cat C and D visibilities ¼ SM. Baro-VNAV and VDP NA when using Salisbury altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -11 °C (13 °F) or above 54 °C (130 °F).

MISSED APPROACH: Climb to 700 then climbing left turn to 2000 direct MAGGO and hold.

ASOS 119.175	PATUXENT APP CON★ 127.95 314.0	Wallops Tower ★ 126.5 (CTAF) 306.975 (CTAF)	GND CON 127.875 269.325
------------------------	--	---	-----------------------------------



CATEGORY	A	B	C	D
LPV DA	330-1	292 (300-1)		
LNAV/ VNAV DA	443-1¼	405 (500-1¼)		
LNAV MDA	420-1	382 (400-1)	420-1½	382 (400-1½)
CIRCLING	600-1	560 (600-1)	620-1½ 580 (600-1½)	860-2¾ 820 (900-2¾)

