

LOC/DME I-EEI

110.35

Chan 40 (Y)

APP CRS

006°

Rwy Ldg

10000

TDZE

896

Apt Elev

896

ILS or LOC RWY 36R

CINCINNATI/NORTHERN KENTUCKY INTL (CVG)

RNP APCH - GPS. From BRCAT or RUPPP or FECTA or SPOOD or DAWGY.
DME or RADAR required. RADAR required for procedure entry at KYKAT.

Simultaneous approach authorized.
For inop ALS, increase S-LOC 36R Cat C and D visibility to 1 3/8 SM.

ALS F-2

MISSED APPROACH: Climb to 1500 then climbing right turn to 4000 direct FLM VOR/DME and hold.

D-ATIS

134.375

CINCINNATI APP CON


119.7 363.15 (090°-269°)
123.875 363.15 (270°-089°)

CINCINNATI TOWER

118.975 360.85 (18L/36R)
118.3 (9/27, 18C/36C)
133.325 (18R/36L)

GND CON

121.7



LAPER I-EEI 11.4 RADAR

TROYF I-EEI 6.7 RADAR

GENVE I-EEI 3.2 RADAR

IM I-EEI 1.8

FLM

VGSI and ILS glidepath not coincident
GENVE (VGSI Angle 3.00/TCH 70).

GS 3.00°
TCH 55

4000

2500

1380

4.8 NM

3.5 NM

1.2 NM

0.1

CATEGORY	A	B	C	D
S-ILS 36R	1096/18 200 (200-1/2)			
S-LOC 36R	1360/24	464 (500-1/2)	1360/50	464 (500-1)
CIRCLING	1460-1	564 (600-1)	1560-1 3/4 664 (700-1 3/4)	1560-2 664 (700-2)

HIRL all Rwy's
TDZ/CL all Rwy's except 27
FAF to MAP 4.9 NM

Knots	60	90	120	150	180
Min:Sec	4:54	3:16	2:27	1:58	1:38