

APP CRS
276°

Rwy Ldg
TDZE
875

Apt Elev
896

CINCINNATI APP CON
119.7 363.15 (090°-269°)
123.875 363.15 (270°-089°)

CINCINNATI TOWER
118.975 360.85 (18L/36R)
118.3 (9/27, 18C/36C)
133.325 (18R/36L)

GND CON
121.7

RNAV (RNP) Z RWY 27
CINCINNATI/NORTHERN KENTUCKY INTL (CVG)

RNP AR APCH - GPS

▼

For uncompensated Baro-VNAV systems, procedure NA below -14°C or above 54°C. For inop ALS, increase RNP 0.15 all Cats visibility to RVR 5500, increase RNP 0.3 all Cats visibility to 1½ SM.

MALSR

MISSED APPROACH: Climb to 3000 direct SEMSE and on track 225° to AVIEW and hold.

D-ATIS 134.375	CINCINNATI APP CON 119.7 363.15 (090°-269°) 123.875 363.15 (270°-089°)	CINCINNATI TOWER 118.975 360.85 (18L/36R) 118.3 (9/27, 18C/36C) 133.325 (18R/36L)	GND CON 121.7
--------------------------	--	---	-------------------------

3000	SEMSE	tr 225°	AVIEW	VGSi and RNAV glidepath not coincident (VGSi Angle 3.00/TCH 67).
CATEGORY	A	B	C	D
RNP 0.15 DA		1244/35	369 (400-½)	
RNP 0.23 DA		1260/35	385 (400-½)	
RNP 0.30 DA		1364/50	489 (500-1)	
AUTHORIZATION REQUIRED				

COVINGTON, KENTUCKY
Amdt 1 12JUN25

CINCINNATI/NORTHERN KENTUCKY INTL (CVG)
39°03'N-84°40'W

RNAV (RNP) Z RWY 27

ELEV 896

D TDZE 875

SE-1, 25 DEC 2025 to 22 JAN 2026

SE-1, 25 DEC 2025 to 22 JAN 2026