

MAYPORT, FLORIDA

WAAS CH 84778 W05A	APCH CRS 049°	Rwy Idg TDZE Arpt Elev	8001 12 15
--------------------------	------------------	------------------------------	------------------

- (USN)

COPTER RNAV (GPS) RWY 5

MAYPORT NS (ADM DAVID L MC DONALD FLD) (KNRB)


RNP APCH	MISSED APPROACH: Climb to 600 then climbing right turn to 1500 direct BINJA and hold.
RADAR required	
* Circling not authorized at night when the VGSI is inop, unless the St. Johns River is clear of vessels from the mouth of Haulover Creek to St. Johns Point. ATC will advise aircraft on final approach if a conflict is present and coordinate a missed approach as required.	

ATIS★ 236.775	JACKSONVILLE APP CON/DEP CON 124.9 308.4	TOWER★ 118.75 239.3	GND CON 126.5 233.7	ASR/PAR
------------------	---	------------------------	------------------------	---------

For uncompensated Baro-VNAV systems,
LNAV/VNAV NA below -15°C or above 54°C.

Max airspeed 90 KIAS.

Visibility Reduction
by Helicopters NA.



EMERG SAFE ALT 100 NM 2800

BINJA		VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 48).		600	1500	BINJA	ELEV 15	TDZE 12
1500	319°	KEENN	049°	RUPER	1100	580	ACKLI	RWY05
GP 3.30° TCH 48				1.5 NM		1.5 NM		
CATEGORY	COPTER							
LPV DA	212-¾	200	(200-¾)					
LNAV/VNAV DA	280-⅞	268	(300-⅞)					
LNAV MDA	400-1	388	(400-1)					
CIRCLING*	560-1	545	(600-1)					

MAYPORT, FLORIDA

30°23'N - 81°25'W MAYPORT NS (ADM DAVID L MC DONALD FLD) (KNRB)

Amdt 1 05SEP24

COPTER RNAV (GPS) RWY 5

SE-3, 25 DEC 2025 to 22 JAN 2026

SE-3, 25 DEC 2025 to 22 JAN 2026