

WAAS CH 42630 W16A	APP CRS 167°	Rwy Idg TDZE 1252 Apt Elev 1252
--	------------------------	---

RNAV (GPS) RWY 16

DRAKE FLD (FYV)

⚠

Baro-VNAV NA when using Springdale altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -17°C (2°F) or above 54°C (130°F). When VGSI inop, Straight-in/Circling Rwy 16 procedure NA at night. Circling NA east of Rwy 16-34. DME/DME RNP-0.3 NA. Visibility reduction by helicopters NA. When local altimeter setting not received, use Springdale altimeter setting and increase all DA and MDA 40 feet. Increase LPV all Cats visibility and LNAV Cats C and D visibility ½ mile and LNAV/VNAV all Cats visibility ⅓ mile. For inop ODALS, increase LPV all Cats visibility ⅓ mile, LNAV/VNAV all Cats visibility ⅓ mile and LNAV Cats C and D visibility ¼ mile. For inop ODALS, when using Springdale altimeter setting, increase LPV all Cats visibility to 1½ miles and LNAV Cats C and D visibility to 2 miles. Inop table does not apply when using Springdale altimeter setting to LNAV/VNAV all Cats and LNAV Cats A and B.

ODALS

MISSED APPROACH:

Climb to 4000 direct OPVIE and on track 181° to VIMXU and hold.

ATIS 119.575	RAZORBACK APP CON★ 121.0 244.575	DRAKE TOWER★ 128.0 (CTAF) 371.9	GND CON 121.8	UNICOM 122.95
------------------------	--	---	-------------------------	-------------------------

(IAF) GENET

3000 NoPT

108°

(11.6)

4 NM

167°

347°

2900

167°

(4.8)

(IF/IAF) ELMIE

3000 NoPT

223°

(16.2)

(IAF) RAZORBACK RZC

3000 NoPT

223°

(16.2)

(FAF) OSETE

1761

1849

1849

1519±

1536

2018

1639±

RW16

2333

1859

1986

MSA RW16 25 NM

4500

Procedure NA for arrivals on RZC

VORTAC airway radials 150 CW 264.

MISSED APCH FIX

OPVIE

181°

(5.5)

VIMXU

181°

4 NM

4 NM Holding Pattern

ELMIE

3000

347°

167°

167°

2900

2080

RW16

4.8 NM

2.5 NM

2.5 NM

GP 3.00° TCH 50

4000

OPVIE

tr 181°

VIMXU

*LNAV only.

OSETE

2900

ZABKO 2.5 NM to RW16

CATEGORY	A	B	C	D
LPV DA		1714-1¾	462 (500-1¾)	
LNAV/VNAV DA		1856-17½	604 (700-1¾)	
LNAV MDA	1900-1	648 (700-1)	1900-1¾	648 (700-1¾)
CIRCLING	2000-1	748 (800-1)	2320-3 1068 (1100-3)	2340-3 1088 (1100-3)

ELEV 1252

D

TDZE 1252

167°

91

TWR 1339

1337

6005 X 100

34

MIRL Rwy 16-34

FAYETTEVILLE, ARKANSAS
Amdt 1C 05OCT23

36°00'N-94°10'W

DRAKE FLD (FYV)

RNAV (GPS) RWY 16

SC-1, 25 DEC 2025 to 22 JAN 2026

SC-1, 25 DEC 2025 to 22 JAN 2026