

WAAS CH 42520 W23A	APP CRS 229°	Rwy Ldg TDZE 1663 Apt Elev 1663
--	------------------------	---

RNAV (GPS) RWY 23

ADIRONDACK RGNL (SLK)

RNP APCH - GPS.

T

A

32°C

Rwy 23 helicopter visibility reduction below 3/4 SM NA. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -29°C or above 54°C. When local altimeter setting not received, procedure NA. Circling Rwy 5, 9, 27 NA at night. Inop table does not apply to LPV DA. For inop ALS, increase LNAV/VNAV all Cats visibility to 1 3/8 SM; increase LNAV Cat A/B visibility to 1 SM.

MALSR

AS

MISSED APPROACH:
Climb to 3500 then climbing right turn to 5500 direct JONNN and hold.

ASOS 124.175	BOSTON CENTER 120.35 342.25	UNICOM 123.0 (CTAF) 0
------------------------	---------------------------------------	---------------------------------

3500 5500 JONNN		RIIKE		JONNN		5 NM Holding Pattern			
HNDRK 3.1 NM to RWY 23		3800		229°		7000 5500			
RWY 23 1.1 NM to RWY 23		2760		3800		GP 3.20° TCH 60			
1.1 NM		2 NM		3 NM		6.7 NM			
CATEGORY	A	B	C	D					
LPV DA	1913-3/4		250 (300-3/4)						
LNAV/VNAV DA	2149-1		486 (500-1)						
LNAV MDA	2100-3/4		437 (500-3/4)						
CIRCLING	2500-1 1/4 837 (900-1 1/4)		2660-1 1/2 997 (1000-1 1/2)		2660-3 997 (1000-3)		2800-3 1137 (1200-3)		

SARANAC LAKE, NEW YORK
Amdt 2 24MAR22

44°23'N-74°12'W

ADIRONDACK RGNL (SLK)

RNAV (GPS) RWY 23

NE-2, 25 DEC 2025 to 22 JAN 2026

NE-2, 25 DEC 2025 to 22 JAN 2026