


WAAS CH 90430 W18B	APP CRS 178°	Rwy Ldg TDZE Apt Elev	5949 34 36
--	------------------------	-----------------------------	---------------------------------------

RNAV (GPS) RWY 18L

VALLEY INTL (HRL)

RNP APCH - GPS.	MISSED APPROACH: Climb to 500 then climbing left turn to 2000 direct RELAX and hold.
Baro-VNAV and VDP NA when using Port Isabel altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -1°C or above 54°C. When local altimeter setting not received, use Port Isabel altimeter setting: increase LPV DA to 276 feet; increase LNAV/VNAV DA to 326 feet and all visibilities ½ SM; increase all MDAs 60 feet and LNAV visibility Cats C and D ¼ SM, and Circling visibility Cat C and D ¼ SM.	

ATIS 124.85	VALLEY APP CON 120.7 279.5	HARLINGEN TOWER ★ 119.3 (CTAF) 0 317.6	GND CON 121.7	UNICOM 122.95
-----------------------	--------------------------------------	--	-------------------------	-------------------------



ELEV 36	D	TDZE 34	500	2000	RELAX	4 NM Holding Pattern
CATEGORY A B C D						
LPV DA 234-¾ 200 (200-¾)						
LNAV/VNAV DA 284-¾ 250 (300-¾)						
LNAV MDA 360-1 326 (400-1)						
CIRCLING 460-1 560-1 600-1½ 680-2						
424 (500-1) 524 (600-1) 564 (600-1½) 644 (700-2)						