

|                |             |                    |
|----------------|-------------|--------------------|
| LOC/DME I-LFT  | APP CRS     | Rwy Ldg            |
| <b>109.5</b>   | <b>216°</b> | <b>7659</b>        |
| Chan <b>32</b> |             | TDZE <b>38</b>     |
|                |             | Apt Elev <b>42</b> |

ILS or LOC RWY 22L  
LAFAYETTE RGNL/PAUL FOURNET FLD (L.F.T)

**VDP NA** with Acadiana Rgnl altimeter setting. When local altimeter setting not received, use Acadiana Rgnl altimeter setting and increase DA to 267 feet; increase all MDA 40 feet and S-LOC 22L visibility Cat C/D to RVR 5000 and Circling visibility Cat C/D ¼ SM. For inop MALSR when using Acadiana Rgnl altimeter setting, increase S-LOC 22L Cat C and D visibility to 1½ mile.

**\*\*RVR 1800 authorized with use of FD or AP or HUD to DA (NA when using Acadiana Rgnl altimeter setting).**

**MALSR**  
A5

**MISSED APPROACH:**  
Climb to 800 then climbing right turn to 2100 on LFT VORTAC R-264 to MICRO INT/ LFT 16 DME and hold.

|                       |                                           |                                                |                         |                         |
|-----------------------|-------------------------------------------|------------------------------------------------|-------------------------|-------------------------|
| ATIS<br><b>134.05</b> | LAFAYETTE APP CON ★<br><b>121.1 363.0</b> | LAFAYETTE TOWER ★<br><b>118.5 (CTAF) 257.8</b> | GND CON<br><b>121.8</b> | UNICOM<br><b>122.95</b> |
|-----------------------|-------------------------------------------|------------------------------------------------|-------------------------|-------------------------|

