

WAAS CH 50503 W22A	APP CRS 216°	Rwy Ldg TDZE 38 Apt Elev 42
--	------------------------	---

RNAV (GPS) RWY 22L

LAFAYETTE RGNL/PAUL FOURNET FLD (L.F'T)

RNP APCH.

▼

▲

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C (5°F) or above 54°C (130°F). VDP NA with Acadiana Rgnl altimeter setting. When local altimeter setting not received, use Acadiana Rgnl altimeter setting and increase all DA 29 feet and all MDA 40 feet; increase LNAV/VNAV visibility all Cats to RVR 3500, increase Circling visibility Cat C/D ½ SM. For inop MALS, increase LNAV Cats C and D visibility ¾ mile. For inop MALS, when using Acadiana Rgnl altimeter setting, increase LNAV/VNAV all Cats visibility to RVR 6000. Baro-VNAV NA when using Acadiana Rgnl altimeter setting.

MALS

AS

MISSED APPROACH:
Climb to 2000 direct
AYOTY and hold.

ATIS 134.05	LAFAYETTE APP CON ★ 121.1 363.0	LAFAYETTE TOWER ★ 118.5 (CTAF) 0 257.8	GND CON 121.8	UNICOM 122.95
-----------------------	---	--	-------------------------	-------------------------

BOZAN

2000
083°
(18.1)

Procedure NA for arrivals at BOZAN
on V222 southwest bound.

(IAF) KEBVE

2000
126°
(8)

(IF) BEDDY

2000
305°
(8)

(IAF) NEYID

2000
315°
(16.4)

MYRIC

MSA RW22L 2.5 NM
2900

Procedure NA for arrivals at MYRIC
on V20 eastbound.

MISSED APCH FIX
AYOTY

036°

216°

4 NM

2000

AYOTY

VGSI and RNAV glidepath not coincident
(VGSI Angle 3.00/TCH 50).

*LNAV only.

1.2

4.8 NM

11.6 NM

2000

216°

2000

GP 3.00°
TCH 54

CATEGORY	A	B	C	D
LPV DA	238/24		200 (200-½)	
LNAV/VNAV DA	349/24		311 (400-½)	
LNAV MDA	480/24	442 (500-½)	480/45	442 (500-¾)
CIRCLING	540-1 498 (500-1)	580-1 538 (600-1)	700-1¾ 658 (700-1¾)	700-2 658 (700-2)

216°

AS

22L

4000 X 7.5

5403 X 1.50

8000 X 1.50

20

TWR

4L

4R

REIL Rwy 4L, 4R, 11, 22R and 29
MIRL Rwy 11-29 and 4L-22R
HIRL Rwy 4R-22L

LAFAYETTE, LOUISIANA
Amdt 1D 23APR20

LAFAYETTE RGNL/PAUL FOURNET FLD (L.F'T)

30°12'N-91°59'W

RNAV (GPS) RWY 22L

SC-4, 25 DEC 2025 to 22 JAN 2026

SC-4, 25 DEC 2025 to 22 JAN 2026