

LOC/DME I-LRU
109.3
Chan 30

APP CRS
307°

Rwy Ldg
TDZE **4444**
Apt Elev **4457**

ILS or LOC RWY 30
LAS CRUCES INTL(LRU)

NA

DME required. When local altimeter setting not received, use Deming altimeter setting: increase DA to 4758 feet and all visibilities ½ mile; increase all MDA 120 feet and visibility Cat C and D ½ mile. VDP NA when using Deming altimeter setting.

MALSR

MISSED APPROACH: Climb to 5100 then climbing left turn to 9000 on heading 139° and on DMN VORTAC R-094 to MOLLY INT/DMN 46.7 DME and hold, continue climb-in-hold to 9000.

AWOS-3
119.025

ALBUQUERQUE CENTER
128.2 285.5

UNICOM
122.7 (CTAF)

MSA LRU 25 NM
10200

LOCALIZER 109.3
I-LRU Chan 30

DEMING 108.6 DMN Chan 23

7700 to JOSPO 083° (39.7)

108.6 DMN Chan 23

ALTERNATE MISSED APCH FIX
MOLLY EWM 24
112.7 TCS R-146 Chan 74
112.4 EWM R-274 Chan 71

4449

(IAF) JOSPO I-LRU 7.4 DMN 39.7

6400 307° (4.9)

(IF) MENDZ I-LRU 12.3

(CFBK M) 7800 NoPT to MENDZ 352° hdg (3.6) and 307° (2.7)

127°

172°

352°

R-094

R-274 112.4 EWM Chan 71

(IAF) MOLLY EWM 24 DMN 46.7

Procedure NA for arrivals at MOLLY on V611 southeast bound.

DME REQUIRED

ELEV 4457 TDZE 4444

REIL Rwy 12
HIRL Rwy 12-30
MIRL Rws 4-22 and 8-26

5100	9000	DMN R-094	MOLLY	JOSPO I-LRU 7.4	Remain within 10 NM
↑	hdg 139°		△		
*LOC only.					
	I-LRU 1.4	*I-LRU 2.2	6400	127°	307°
			6400		6400
	-0.7 NM	5.3 NM			GS 3.00° TCH 47
CATEGORY	A	B	C	D	
S-ILS 30	4644-½ 200 (200-½)				
S-LOC 30	4720-½ 276 (300-½)				
CIRCLING	4900-1 443 (500-1)	5040-1 583 (600-1)	5320-2½ 863 (900-2½)	5320-2¾ 863 (900-2¾)	

LAS CRUCES, NEW MEXICO
Amdt 3A 08DEC16

32°17'N-106°55'W

LAS CRUCES INTL(LRU)
ILS or LOC RWY 30