

2527.5

RNAV (GPS) RWY 36
DUBUQUE RGNL (DBQ)

T For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -17°C or above 46°C. Baro-VNAV and YDP NA when using Monticello altimeter setting. When local altimeter setting not received, use Monticello altimeter setting and increase all DA 88 feet and all MDA 100 feet, increase LNAV/VNAV all Cats, LNAV Cats C and D and Circling Cat C visibility ¼ mile. For inop MALSR when using Monticello altimeter setting, increase LPV all Cats visibility to RVR 5000.

A # RVR 1800 authorized with use of FD or AP or HUD to DA, NA when using Monticello altimeter setting.

MISSED APPROACH:
Climb to 3000 direct
WABKU and via 314°
track to CASSY and hold.

MISSED APCH FIX

CASSY 143° 4 NM

WABKU

(not to scale)

ANOSA 073° (23)

(IAF) JUGIT 087° (5)

(IF/IAF) DIVE 357° (6.2)

(FAF) LATCI 1377

DUBUQUE DBQ 1229±

2700 to DIVE 178° (11.8)

RW36 1104

2700 NoPT 087° (5)

2700 NoPT 267° (5)

(IAF) NEGUE

357° 177° 4 NM

2700 350° (16.3)

LOTTE

MSA RW36 25 NM 2900

ELEV 1077	TDZE 1048
-----------	-----------

HIRL Rwy 13-31 and 18-36

REIL Rwy 18

DUBUQUE RGNL (DBQ)
RNAV (GPS) RWY 36

NC-3, 25 DEC 2025 to 22 JAN 2026

NC-3, 25 DEC 2025 to 22 JAN 2026