

APP CRS	Rwy Ldg	5998
229°	TDZE	184
	Apt Elev	187

RNAV (RNP) Y RWY 23

MORRISTOWN MUNI (MMU)

RNP AR APCH - GPS. Authorization required. From HOLEM: RF

When local altimeter setting not received, procedure NA. For uncompensated Baro-VNAV systems, procedure NA Below -15°C or above 54°C. For inop ALS, increase RNP 0.11 all Cats visibility to 1 SM and RNP 0.30 all Cats visibility to 1¼ SM.

MALSR

AS

MISSED APPROACH: Climb to 2000 direct SUCSO then on track 250° to SBJ VOR/DME and hold.

ATIS 124.25	NEWARK APP CON 127.6 379.9	MORRISTOWN TOWER★ 118.1 0 (CTAF) 353.9	GND CON 134.2
----------------	-------------------------------	---	------------------

(IAF) STILLWATER STW 210K

3000 133° (10.1)

ELIZE 3000 123° (8.1)

FIGON 2000 057° (5.9)

(IF) HOLEM 180K 2000 057° (5.9)

(FAF) BINGG 2000 229° (6.1)

RW23 229° (5.5)

SUCSO 250° (12.5)

(IAF) SOLBERG SBJ 210K 3000 045° (20)

MISSED APCH FIX

SOLBERG SBJ 210K 250° 070° 4 NM

Procedure NA for arrival on SBJ VOR/DME airway radials 028 CW 117.

ELEV 187 **TDZE 184**

229°

3997 X 150

5998 X 150

TWR 252

31

GP 3.00° TCH 55

5.5 NM

CATEGORY	A	B	C	D
RNP 0.11 DA		553-5/8	369 (400-5/8)	
RNP 0.30 DA		808-13/8	624 (700-13/8)	

AUTHORIZATION REQUIRED

MORRISTOWN, NEW JERSEY

Amtd 1 27NOV25

40°48'N - 74°25'W

MORRISTOWN MUNI (MMU)

RNAV (RNP) Y RWY 23