

WAAS CH 77805 W23A	APP CRS 231°	Rwy Ldg TDZE 141 Apt Elev 142
--	------------------------	---


RNAV (GPS) RWY 23
LAKELAND LINDER INTL (LAL)

RNP APCH.

▼ For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C or above 54°C. When local altimeter setting not received, use Plant City altimeter setting: increase LPV DA to 444 feet; increase LNAV/VNAV DA to 540 feet; increase all MDAs 20 feet and LNAV Cat C/D and Circling Cat C visibility ½ SM. Baro-VNAV and VDP NA when using Plant City altimeter setting. Rwy 23 helicopter visibility reduction below ¾ SM NA. Circling NA to Rwy's 8 and 26.

MISSED APPROACH: Climb to 2000 direct BIYAT and right turn on track 330° to MIREE then on track 014° to PLUMY and hold.

ATIS 118.025	TAMPA APP CON 120.65 290.3	LAKELAND TOWER 124.5 236.775	GND CON 121.4
------------------------	--------------------------------------	--	-------------------------



ELEV 142 TDZE 141

TDZ/CL Rwy 10
HIRL Rwy's 5-23 and 10-28

2000 BIYAT tr 330° MIREE tr 014° PLUMY

VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 46).

5 NM Holding Pattern

JOVMU

051° 6000 2700

GP 3.00° TCH 50

1.7 NM to RW23

OBTOQ 1700

231° 1700

1.7 NM 3 NM 6.1 NM

CATEGORY	A	B	C	D
LPV DA	426-1 285 (300-1)			
LNAV/VNAV DA	522-1¼ 381 (400-1¼)			
LNAV MDA	720-1 579 (600-1)	720-1½ 579 (600-1½)	720-1¾ 579 (600-1¾)	
CIRCLING	720-1 578 (600-1)	720-1½ 578 (600-1½)	840-2¼ 698 (700-2¼)	

SE-3, 25 DEC 2025 to 22 JAN 2026

SE-3, 25 DEC 2025 to 22 JAN 2026