

ILS Z or LOC/DME Z RWY 6

LOC I-EDF **APCH CRS** **Rwy Idg** **10,000**
110.3 **062°** **TDZE** **175**
Arpt Elev **213**

[USAF] **ELMENDORF AFB (PAED)**

***When TDZ/CL lights inop increase RVR to 24.**
When ALS inop, increase RVR to 40, vis to ½ mile.

ATIS ★ **ANCHORAGE APP CON** **TOWER** **GND CON** **CLNC DEL** **PAR**
124.3 273.5 **118.6 290.5 (N)** **127.2 352.05** **121.8 275.8** **128.8 306.925** **PAR**
123.8 259.3 (S)

**** When ALS inop, increase CAT AB RVR to 55, vis to 1 mile, CAT CDE vis to 1 ¼ miles.**
***** Circling not authorized S of Rwy 6-24.**
****** Circling not authorized SW of Rwy 6 and 34.**

EDF DME available on 113.4
CAUTION: Descent gradient after FEDNO is greater than descent gradient between SEKKA to FEDNO.
CAUTION: Intense VFR aircraft operations in the vicinity of EDF final.
CAT E aircraft remain within 4.5 NM of runway when executing circling maneuver.

(IAF) HYSN TED 11 3000
(IF) SSNOW EDF 11.2 TED 6.4
SEKKA EDF 6.5 1600 213
FEDNO EDF 4.2 336
ELMENDORF Chan 81 EDF
LOCALIZER 110.3 I-EDF
ANCHORAGE INTL
ANCHORAGE 113.15 TED 11 Chan 78 (Y)

EMERG SAFE ALT 100 NM 15,300

HYSON TED 11 3000
SSNOW EDF 11.2 TED 6.4
SEKKA EDF 6.5 1600
FEDNO EDF 4.2 336
EGKIL EDF 2.8 900
BQG R-138
VGSI and ILS glidepath not coincident (VGSI Angle 3.00/TCH 77). EDF TACAN
GS 3.00° TCH 57
2.3 NM 1.4 NM 0.6

CATEGORY	A	B	C	D	E
S-ILS 6 *	375/18		200	(200-½)	
S-LOC 6 **	600/24 425 (400-½)		600/40	425	(400-¾)
*** CIRCLING	840-1	627 (700-1)	840-1¾ 627 (700-1¾)	840-2 627 (700-2)	940-2½ 727 (800-2½)
RWY 34 CIRCLING MINIMUMS					
**** CIRCLING	840-1	627 (700-1)	920-2 707 (800-2)	1020-2½ 807 (900-2½)	1480-3 1267 (1300-3)

HIRL Rwy 6-24 TDZ/CL Rwy 6

AK, 27 NOV 2025 to 22 JAN 2026

AK, 27 NOV 2025 to 22 JAN 2026