



WAAS CH 70507 W19A	APP CRS 193°	Rwy Ldg 6400 TDZE 120 Apt Elev 129
--	------------------------	---

RNAV (GPS) RWY 19R

BETHEL (BET)(PABE)

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -25°C (-13°F) or above 54°C (130°F). Circling NA west of Rwy 1L-19R. DME/DME RNP-0.3 NA.		MALSR	MISSED APPROACH: Climb to 1700 then climbing right turn to 2000 direct ROLL and hold.
ATIS 119.8	ANCHORAGE CENTER 125.2 372.0	BETHEL TOWER ★ 118.7 (CTAF) 0	GND CON 121.7



ELEV 129 TDZE 120		1700	2000	ROLLR
		↑	↷	△
		* LNAV only		
		* 1.3 NM to RWY19R		
		RWY19R		
		1.3 NM 3.9 NM 6.7 NM		
		KAYSE 1800 CATUB 4 NM Holding Pattern		
		193° 013° 1800 193°		
		GP 3.00° TCH 52		
CATEGORY	A	B	C	D
LPV DA	320/24 200 (200-½)			
LNAV/VNAV DA	479/40 359 (400-¾)			
LNAV MDA	560/24	440 (500-½)	560/45	440 (500-¾)
CIRCLING	560-1 431 (500-1)	600-1 471 (500-1)	600-1½ 471 (500-1½)	680-2 551 (600-2)