

WAAS CH 42707 W01A	APP CRS 012°	Rwy Ldg 6400 TDZE 127 Apt Elev 129
--	------------------------	---

RNAV (GPS) RWY 1L

BETHEL (BET)(PABE)


▼

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -25°C (-13°F) or above 54°C (130°F).
Circling NA west of Rwy 1L-19R. DME/DME RNP-0.3 NA.
For inop ALS, increase LNAV Cat C/D visibility to RVR 6000.

MALSR

MISSED APPROACH: Climb to 2000
direct KUSKM and left turn on track
257° to ROLLR and hold.

ATIS 119.8	ANCHORAGE CENTER 125.2 372.0	BETHEL TOWER ★ 118.7 (CTAF) 0	GND CON 121.7
----------------------	--	---	-------------------------



VGSI and RNAV glidepath not coincident
(VGSI Angle 3.00/TCH 39).

4 NM Holding Pattern

ROMAC

2000

192°

012°

GP 3.00°
TCH 47

1800

012°

6 NM

3.9 NM

1.1 NM

2000

KUSKM

ROLLR

tr 257°

*LNAV only

*1.1 NM to RW01L

RW01L

CATEGORY	A	B	C	D
LPV DA		377/24	250 (300-½)	
LNAV/VNAV DA		555/50	428 (500-1)	
LNAV MDA	500/24	373 (400-½)	500/50	373 (400-1)
CIRCLING	500-1 371 (400-1)	600-1 471 (500-1)	600-1½ 471 (500-1½)	680-2 551 (600-2)

ELEV 129 D TDZE 127

HIRL Rwy's 1L-19R, 1R-19L and 12-30 0

REIL Rwy's 1R and 19L 0