

WAAS CH 82004 W05A	APP CRS 050°	Rwy Ldg 10960 TDZE 93 Apt Elev 93
--	------------------------	--

RNAV (GPS) RWY 5

KINSTON RGNL JETPORT AT STALLINGS FLD (ISO)

RNP APCH - GPS.

V For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C or above 54°C. Baro-VNAV and VDP NA when using GSB altimeter setting. When local altimeter setting not received, use GSB altimeter setting: increase LPV DA to 336 feet; increase LNAV/VNAV DA to 529 feet and all visibilities to RVR 4000; increase all MDAs 60 feet and LNAV visibility Cat C/D to RVR 4500 and Circling visibility Cat D ¼ SM. For inop ALS, increase LNAV/VNAV all Cats visibility to RVR 4500 and LNAV Cats A and B visibility to RVR 5500 and Cats C and D to RVR 6000. For inop ALS when using GSB altimeter setting, increase LNAV Cats A and B visibility to RVR 5500 and Cats C and D to 1 ½ mile.



* RVR 1800 authorized with use of FD or AP or HUD to DA (NA when using GSB altimeter setting).

MALSr




MISSED APPROACH:
Climb to 2500 direct
WINTI and hold.

AWOS-3 132.75	SEYMOUR JOHNSON APP CON ★ 127.3 273.6	KINSTON TOWER ★ 120.6 (CTAF) 0 335.55	GND CON 121.9	UNICOM 122.95
-------------------------	---	---	-------------------------	-------------------------



CATEGORY		A	B	C	D
LPV	DA*	293/24		200 (200-½)	
LNAV/ VNAV	DA	486/35		393 (400-¾)	
LNAV	MDA	480/24 387 (400-½)		480/35 387 (400-¾)	
CIRCLING		580-1 487 (500-1)		700-1¾ 607 (700-1¾)	740-2 647 (700-2)



RNAV (GPS) RWY 5