

VORTAC SZW	APP CRS	Rwy Idg	7000
117.5	173°	TDZE	83
Chan 122		Apt Elev	83

VOR RWY 18

TALLAHASSEE INTL (TLH)

ASR

Helicopter visibility reduction below ¾ SM NA.
VDP NA with Bainbridge altimeter setting.

MISSED APPROACH: Climb to 1500 then climbing right turn to 3000 direct SZW VORTAC and hold.

ATIS	TALLAHASSEE APP CON	TALLAHASSEE TOWER	GND CON	CLNC DEL	UNICOM
119.45 239.25	135.8 317.4	118.7 (CTAF) 257.8	121.9 348.6	126.65 275.8	123.075

One Minute Holding Pattern				
3000 ← 353° → 173° →				
*880 when using Bainbridge altimeter setting.				
6.6 NM 0.8 NM 1.2 NM				
CATEGORY	A	B	C	D
S-18	780-1	697 (700-1)	780-2	697 (700-2)
CIRCLING	780-1	697 (700-1)	780-2	800-2¼
			697 (700-2)	717 (800-2¼)
WAPIM FIX MINIMUMS				
S-18	540-1	457 (500-1)	540-1¾	457 (500-1¾)
CIRCLING	580-1	600-1	640-1½	800-2¼
	497 (500-1)	517 (600-1)	557 (600-½)	717 (800-2¼)

TALLAHASSEE, FLORIDA

Amdt 12C 16JUL20

30°24'N-84°21'W

TALLAHASSEE INTL (TLH)

VOR RWY 18