

WAAS CH 61106 W20A	APP CRS 197°	Rwy Idg TDZE 442 Apt Elev 444
--	------------------------	---

RNAV (GPS) RWY 20

BREMERTON NTL (PWT)

RNP APCH.

⚠

Circling NA for Cats C and D west of Rwy 2-20. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C or above 54°C. Baro-VNAV and VDP NA when using Seattle-Tacoma Intl altimeter setting. When local altimeter setting not received, use Seattle-Tacoma Intl altimeter setting and increase all DA 45 feet and all MDA 60 feet; increase LNAV Cat A and increase Circling Cats C/D visibility ½ SM. Inop table does not apply to LNAV/VNAV all Cats.

MALSR

⬆


AS


⬆

⬆

MISSED APPROACH:
Climb to 4000 direct CEBOD and on track 170° to CARRO and hold, continue climb-in-hold to 4000.

AWOS-3PT 121.2	SEATTLE APP CON 120.1 254.4 269.125	CLNC DEL 127.1	UNICOM 123.05 (CTAF) 0
--------------------------	---	--------------------------	---



4000	CEBOD	tr 170°	CARRO				
*LNAV only				*2.5 NM to RW20			
							
CATEGORY				A	B	C	D
LPV	DA	642-½ 200 (200-½)					
LNAV/ VNAV	DA	1396-4 954 (1000-4)					
LNAV	MDA	1300-½ 858 (900-½)	1300-¾ 858 (900-¾)	1300-2 858 (900-2)			
C CIRCLING		1300-1¼ 856 (900-1¼)	1300-2½ 856 (900-2½)		1300-2¾ 856 (900-2¾)		

