

LOC H/LBE

110.9

APP CRS

236°

Rwy Idg

7372

TDZE

1145

Apt Elev

1199

ILS or LOC RWY 24

ARNOLD PALMER RGNL (LBE)

RNAV 1-GPS or RADAR required for procedure entry.
From IGOCI: RNAV 1-GPS required.
RADAR required.

MALSR

MISSED APPROACH: Climb to 2000 then climbing right turn to 5000 direct AGC VOR/DME and hold.

Circling NA SE of Rwy 6-24. Inop table does not apply to S-LOC 24 Cats C/D.
For inop ALS, increase POSER OM minimums S-LOC 24 Cats C/D visibility to 1 3/4 SM.

ATIS	JOHNSTOWN APP CON ★	PALMER TOWER ★	GND CON
118.375	121.2 299.2	125.0 (CTAF) 0	121.8

2000

5000

AGC

One Minute Holding Pattern

ELEV 1199

TDZE 1145

CATEGORY	A	B	C	D
S-ILS 24		1345-1/2	200 (200-1/2)	
S-LOC 24	2380-3/4 1235 (1200-3/4)	2380-1 1235 (1200-1)	2380-3 1235 (1200-3)	
CIRCLING	2380-1 1/4 1181 (1200-1 1/4)	2380-1 1/2 1181 (1200-1 1/2)	2380-3 1181 (1200-3)	
POSER OM MINIMUMS				
S-LOC 24	1760-1/2 615 (600-1/2)	1760-13/8 615 (600-13/8)		
CIRCLING	1760-1 561 (600-1)	1780-1 581 (600-1)	2060-2 1/2 861 (900-2 1/2)	2060-2 3/4 861 (900-2 3/4)

LATROBE, PENNSYLVANIA

Amdt 17C 17JUN21

40°16'N-79°25'W

ARNOLD PALMER RGNL (LBE)

ILS or LOC RWY 24