

WAAS CH 78338 W02A	APP CRS 020°	Rwy Ldg TDZE 299 Apt Elev 311
--	------------------------	---

RNAV (GPS) RWY 2
W H 'BUD' BARRON (DBN)



▼ Night landing: Rwy 32 NA. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C (5°F) or above 54°C (130°F). Baro-VNAV and VDP NA when using Vidalia altimeter setting. DME/DME RNP-0.3 NA. When local altimeter setting not received, use Vidalia altimeter setting and increase LPV DA to 593 feet and LNAV/VNAV DA to 849 feet and all MDA 100 feet; increase LNAV/VNAV all Cats visibility ¾ mile and LNAV Cats C/D visibility and Circling Cats C/D visibility ¼ mile. For inop MALSR, increase LNAV Cat C/D visibility to 1 ½ mile. For inop MALSR when using Vidalia altimeter setting, increase LPV all Cats visibility to 1 mile, LNAV/VNAV all Cats visibility to 1 ½ mile and LNAV Cat C/D visibility to 1 ¾ mile.

MALSR




MISSED APPROACH:
Climb to 2000 direct VOLVY and hold.

AWOS-3 118.425	ATLANTA APP CON ★ 124.2 279.6	UNICOM 122.7 (CTAF) 
--------------------------	---	---



CATEGORY	A	B	C	D
LPV DA		499-1½	200 (200-½)	
LNAV/VNAV DA		755-1⅛	456 (500-1⅛)	
LNAV MDA	700-½ 401 (400-½)		700-¾ 401 (400-¾)	
CIRCLING	760-1 449 (500-1)	780-1 469 (500-1)	1020-2 709 (800-2)	1020-2¼ 709 (800-2¼)



SE-4, 25 DEC 2025 to 22 JAN 2026

SE-4, 25 DEC 2025 to 22 JAN 2026