

WAAS CH 77507 W29A	APP CRS 294°	Rwy Ldg TDZE 531 Apt Elev 544
--	------------------------	---

RNAV (GPS) RWY 29

ST LOUIS RGNL (ALN)


RNP APCH.

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -16°C or above 54°C. For inop ALS, increase LNAV/VNAV all Cats visibility to ¾ SM and LNAV Cat C/D visibility to 1 SM.

MALSR

MISSED APPROACH:
Climb to 2400 direct
SQUAR and hold.

ATIS 128.0	ST LOUIS APP CON 124.2 353.9	REGIONAL TOWER★ 126.0(CTAF) 0 239.0	GND CON 120.2	UNICOM 122.95
----------------------	--	---	-------------------------	-------------------------



ELEV **544** **D** TDZE **531**

REIL Rwy 11 1
HIRL Rwy 11-29 1
MIRL Rwy 17-35 1

Diagram showing the approach path for RWY 29, including the TWR, 8099 X 150, 6500 X 100, and 35 markers.

2400 SQUAR				
*LNAV only.				
Diagram showing the approach path for RWY 29, including the DIYEL, OSERE, and QUNIE fixes, and the holding pattern at QUNIE.				
CATEGORY	A	B	C	D
LPV DA	731-½		200 (200-½)	
LNAV/VNAV DA	825-½		294 (300-½)	
LNAV MDA	900-½	369 (400-½)	900-¾	369 (400-¾)
CIRCLING	1000-1	456 (500-1)	1160-1¾ 616 (700-1¾)	1200-2 656 (700-2)