

WAAS CH 82537 W24A	APP CRS 243°	Rwy Ldg TDZE Apt Elev	5799 719 722
--	------------------------	-----------------------------	---



RNAV (GPS) RWY 24

COLES COUNTY MEML (MTO)

⚠ DME/DME RNP-0.3 NA. When local altimeter setting not received, use Champaign/Urbana altimeter setting and increase all DA 82 feet, increase all MDA 100 feet, increase LPV all Cats visibility $\frac{1}{8}$ mile, LNAV/VNAV all Cats, LNAV Cats C/D and Circling Cat D visibility $\frac{1}{4}$ mile. Baro-VNAV and VDP NA when using Champaign/Urbana altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -19°C (-2°F) or above 54°C (130°F). Circling NA to Rwy's 18 and 36.

MISSED APPROACH: Climb to 1200 then climbing right turn to 3000 direct WUBTA and hold.

ASOS 118.475	CHAMPAIGN APP CON★ 132.85 290.225	UNICOM 122.7 (CTAF) 0
------------------------	---	---------------------------------



	1200	3000	WUBTA	
	* LNAV only.			
	1.1 NM	3.7 NM	6.1 NM	
	1.1 NM	3.7 NM	6.1 NM	
CATEGORY	A	B	C	D
LPV DA	969-7/8 250 (300-7/8)			
LNAV/VNAV DA	1017-1 298 (300-1)			
LNAV MDA	1120-1 408 (500-1)	1120-1 408 (500-1 1/8)		
CIRCLING	1160-1 438 (500-1)	1180-1 458 (500-1)	1240-1 518 (600-1 1/2)	1380-2 658 (700-2)