

LOC/DME I-ANE	APP CRS	Rwy Ldg
111.15	269°	5000
Chan 48 (Y)		TDZE 910
		Apt Elev 912

ILS or LOC RWY 27

ANOKA COUNTY/BLAINE (JANES FLD) (ANE)

DME required. RADAR required for procedure entry at BLAYN.

⚠

VDP NA when using Crystal altimeter setting. When local altimeter setting not received, use Crystal altimeter setting and increase S-ILS 27 DA to 1131 feet; increase all MDAs 40 feet and S-LOC 27 visibility Cat C/D ¼ SM, and Circling visibility Cat D ¼ SM. For inop ALS when using Crystal altimeter setting, increase S-LOC 27 Cat C/D visibility to 1 ½ SM.

MALSR

MISSED APPROACH: Climb to 2700 direct GEP VORTAC and hold, continue climb-in-hold to 2700.

ATIS	MINNEAPOLIS APP CON	ANOKA TOWER★	GND CON	UNICOM
120.625	126.5 335.65	132.4 (CTAF) 0	121.85	122.95

The main chart displays the ILS/LOC RWY 27 approach. Key features include:

- ILS/LOC 27** with a frequency of 111.15 MHz and channel 48 (Y).
- Localizer** course aligned with the runway, with a frequency of 111.15 MHz and channel 48 (Y).
- Approach Path** starting at 3100 feet, descending to 2600 feet, and then to 1780 feet.
- Altitudes** at various points: 3100, 2600, 1780, 1082, 3500 (MSA GEP 25 NM).
- Navigation Aids** including GEP (3100), BOKYA (6.2), KOGGE (3.6), and JUDAL (16.7).
- Obstacles** marked with their MSL altitudes and distances from the course.
- Procedure NA** for arrivals at STILS on V78 eastbound.

ELEV 912

TDZE 910

Diagram of the airport layout showing runways, taxiways, and other features. Key elements include:

- Runways**: 81, 36, 27.
- taxiways**: 4855 X 100, 5000 X 100.
- Obstacles**: TWR, 36, 269°.
- ILS/LOC 27** with a frequency of 111.15 MHz and channel 48 (Y).
- Localizer** course aligned with the runway, with a frequency of 111.15 MHz and channel 48 (Y).

HIRL Rwy 9-27 0

MIRL Rwy 18-36 0

REIL Rwys 9, 18, and 36 0

FAF to MAP 5.2 NM

Knots	60	90	120	150	180
Min:Sec	5:12	3:28	2:36	2:05	1:44

2700	GEP	Use I-ANE DME when on the localizer course.				JUDAL I-ANE 16.7
↑		KOGGE I-ANE 3.6	BOKYA I-ANE 6.2	2600	2600	3100
		I-ANE 1	I-ANE 2.2	1780	2600	3100
		1.2 NM	1.4 NM	2.6 NM	10.5 NM	GS 3.00° TCH 49
CATEGORY	A	B	C	D		
S-ILS 27	1110-½ 200 (200-½)					
S-LOC 27	1340-½	430 (500-½)	1340-¾	430 (500-¾)		
CIRCLING	1400-1	488 (500-1)	1420-1½	1580-2	508 (600-1½)	668 (700-2)

MINNEAPOLIS, MINNESOTA

ANOKA COUNTY/BLAINE (JANES FLD) (ANE)

ILS or LOC RWY 27

Amdt 1 08SEP22

45°09'N-93°13'W