

LOC I-JBR <u>110.15</u>	APP CRS 230°	Rwy Ldg 6200 TDZE 262 Apt Elev 262
-----------------------------------	------------------------	---

ILS or LOC RWY 23

JONESBORO MUNI (JBR)

T Circling NA northwest of Rwy 5-23. Rwy 23 helicopter visibility reduction below $\frac{3}{4}$ SM NA. When local altimeter not received, use Walnut Ridge altimeter setting; increase DA to 600 feet and all visibilities $\frac{1}{8}$ SM; increase all MDAs 60 feet. S-LOC 23 Cat C/D visibility $\frac{1}{8}$ SM and Circling Cat C $\frac{1}{8}$ SM. For inop ALS, increase S-ILS 23 Cat A/B visibility to $\frac{1}{8}$ SM and S-LOC 23 Cat C/D to $\frac{1}{8}$ SM. For inop ALS when using Walnut Ridge altimeter setting, increase S-ILS 23 Cat A/B visibility to 1 SM. When using Walnut Ridge altimeter setting, inop table does not apply to S-LOC 23 Cats C/D. Circling Rwy 31 NA at night.



ODALS



MISSED APPROACH:
Climb to 2000 then
climbing left turn to
2300 direct JBR
VOR/DME and hold.

ASOS
118,525

MEMPHIS CENTER
120.075 289.4

UNICOM
123.0 (CTAF) **L**

JONESBORO, ARKANSAS

Amdt 2C 25MAR21

35°50'N-90°39'W

JONESBORO MUNI (JBR)

ILS or LOC RWY 23