


VORTAC GJ	APP CRS	Rwy Ldg
115.4	102°	6500
Chan 101	TDZE	777
	Apt Elev	778


VOR RWY 9
ELKHART MUNI (EKM)

DME required.	MISSED APPROACH: Climb to 2500 on GJ R-101 to SKEAT/GJ 20 DME and hold.
⚠ VDP NA when using SBN altimeter setting. Rwy 9 helicopter visibility reduction below ¼ SM NA. ⚠ Circling NA to Rwy 8 and 26. When local altimeter setting not received, use SBN altimeter setting and increase all MDAs 40 feet and S-09 visibility Cat C/D ½ SM, and Circling visibility Cat D ¼ SM. Circling Rwy 18 and 36 NA at night.	

AWOS-3 124.475	SOUTH BEND APP CON ★ 118.55 257.8	ELKHART TOWER ★ 119.5 (CTAF) 0	GND CON 121.8	UNICOM 122.95
--------------------------	---	--	-------------------------	-------------------------



One Minute Holding Pattern	GJ VORTAC	SALIM GJ [8.8]	2500	GJ R-101	SKEAT GJ [20]
10000 2500	282° 102°	102° 2500	3.20° TCH 49	GJ [12.1] GJ [13.7]	
VGSI and descent angles not coincident (VGSI Angle 3.00/TCH 38).					
8.8 NM 3.3 NM 1.7					
CATEGORY	A	B	C	D	
S-9	1340-1	563 (600-1)	1340-1½	563 (600-1½)	
CIRCLING	1340-1	562 (600-1)	1380-1¾ 602 (700-1¾)	1580-2½ 802 (900-2½)	



EC-2, 25 DEC 2025 to 22 JAN 2026

EC-2, 25 DEC 2025 to 22 JAN 2026