

WAAS CH 87011 W20A	APP CRS 197°	Rwy Ldg TDZE 25 Apt Elev 26
--	------------------------	---

RNAV (GPS) RWY 20

PITT-GREENVILLE (PGV)



RNP APCH - GPS.

⚠ Baro-VNAV NA when using Washington altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C or above 50°C. When local altimeter setting not received use Washington altimeter setting and increase LPV DA to 272 feet; increase LNAV/VNAV DA to 345; increase all MDAs 60 feet and Circling visibility Cat D ¼ SM. For inop ALS, increase LNAV/VNAV all Cats visibility to ¾ mile and LNAV all Cats visibility to 1 mile. For inop ALS when using Washington altimeter setting, increase LNAV/VNAV all Cats visibility ½ SM, and LNAV visibility Cat A/B ¼ SM. Rwy 20 helicopter visibility reduction below ¾ SM NA.

MALSR

MISSED APPROACH:
Climb to 3100 direct BOWBO and hold, continue climb-in-hold to 3100.

AWOS-3 128.425	WASHINGTON CENTER 123.85 279.65	UNICOM 122.8 (CTAF) 0
--------------------------	---	---------------------------------



3100	BOWBO	TROTH 1.5 NM to RW20	EVAXY 1400	KENIR 4 NM Holding Pattern	017° → 2100
*LNAV only					← 197°
		540*	1400		GP 3.00° TCH 50
	1.5 NM	2.7 NM	9.6 NM		
CATEGORY	A	B	C	D	
LPV DA		231-1½	205 (300-½)		
LNAV/VNAV DA		304-¾	278 (300-¾)		
LNAV MDA		400-¾	374 (400-¾)		
CIRCLING	600-1 574 (600-1)	620-1 594 (600-1)	700-2 674 (700-2)	800-2½ 774 (800-2½)	

SE-2, 25 DEC 2025 to 22 JAN 2026

SE-2, 25 DEC 2025 to 22 JAN 2026