

WAAS CH 99701 W24A	APP CRS 240°	Rwy Idg TDZE Apt Elev	5500 545 547
--	------------------------	-----------------------------	---

RNAV (GPS) RWY 24

MUSCATINE MUNI (MUT)

RNP APCH

▼

▲

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -16°C (4°F) or above 48°C (118°F). For inop ALS, increase LPV all visibilities to 1 SM, increase LNAV/VNAV all Cats and LNAV Cats C visibility to 1½ SM, and increase LNAV Cat D visibility to 1¼ SM. When local altimeter setting not received, use Iowa City altimeter setting and increase LPV DA to 992 and all visibilities ½ SM; increase LNAV/VNAV DA to 1030 feet and all visibilities ¼ SM; increase all MDA 80 feet and LNAV Cats C and D visibility ¼ SM and Circling Cat C visibility ¼ SM. For inop ALS when using Iowa City altimeter setting, increase LPV all visibilities to 1 SM, LNAV/VNAV all visibilities to 1¾ SM, LNAV Cats A and B visibility to 1 SM, and LNAV Cats C and D visibility to 1¾ SM. Baro-VNAV and VDP NA when using Iowa City altimeter setting.


MALSR

AS

⋮

MISSED APPROACH:
Climb to 3000 direct
IZBUF and hold.

AWOS-3P 120.625	QUAD CITY APP CON * 133.275 257.8	CLNC DEL 119.125	UNICOM 122.7 (CTAF) 0
---------------------------	---	----------------------------	---------------------------------



3000 IZBUF		YELDU 2.1 NM to RW24		JOLIX		EDAGE		5 NM Holding Pattern	
*LNAV only		*1.2 NM to RW24		1260*		2300		GP 3.00° TCH 55	
1.2		0.9		3.2 NM		6 NM			
CATEGORY		A		B		C		D	
LPV DA		812-½		267 (300-½)					
LNAV/VNAV DA		950-¾		405 (500-¾)					
LNAV MDA		960-½ 415 (500-½)		960-¾ 415 (500-¾)		960-1 415 (500-1)			
CIRCLING		1080-1¼ 533 (600-1¼)		1200-1¼ 653 (700-1¼)		1200-1¾ 653 (700-1¾)		1500-3 953 (1000-3)	

ELEV 547

TDZE 545

REIL Rwy 6, 12, and 30 0

MIRL Rwy 6-24 and 12-30 0