

APP CRS
137°

Rwy Ldg
TDZE
27

Apt Elev
29

RNAV (RNP) Y RWY 14

JACKSONVILLE INTL (JAX)

▼

For uncompensated Baro-VNAV systems, procedure NA below -5°C (23°F) or above 54°C (130°F). GPS required. For inoperative MALS, increase RNP 0.30 all Cats

MALS

MISSED APPROACH: Climb to 500 then climbing left turn to 2000 direct YEJWO and hold.

D-ATIS 125.85	JACKSONVILLE APP CON 119.0 269.9	JACKSONVILLE TOWER 118.3 317.7	GND CON 121.9 348.6
-------------------------	--	--	-------------------------------

RNAV (RNP) Y RWY 14 chart details:

- Waypoints and Altitudes: ORTAR (3000), DIPDE (3000), AMLIA, JOVFE, AHMIV, KRISO, EYLND (4000), DEDDA (3000), PENSE, NARDE.
- Distances and Angles: 1800/139° (4.8), 1500/100° (5.2), 1500/100° (5.2), 1100/130° (3.3), 1100/110° (5.5), 137°/134± (3.2), 2300/035° (6), 2000/040° (3.6), 1100/110° (5.5).
- MSA: RW14 25 NM, 2700.
- MISSED APCH FIX: YEJWO, 4 NM, 077°/257°.

VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 70).

500 2000 YEJWO

GP 3.00° TCH 54

1100 137°

See planview for multiple IF locations.

3.2 NM

CATEGORY	A	B	C	D
RNP 0.30 DA	389-1 362 (400-1)			

AUTHORIZATION REQUIRED

REIL Rwy 32
TDZL/RCLS Rwy 8, 14, and 26
HIRL Rwy 8-26 and 14-32

JACKSONVILLE, FLORIDA

Orig-B 30APR15

30°30'N-81°41'W

JACKSONVILLE INTL (JAX)

RNAV (RNP) Y RWY 14