



WAAS CH 42717 W20A	APP CRS 196°	Rwy Idg TDZE Apt Elev	5001 571 580
--	------------------------	-----------------------------	---

RNAV (GPS) RWY 20

HENRY COUNTY (PHT)

RNP APCH - GPS.		MISSED APPROACH: Climb to 2300 direct WASED and hold.
▼ ▲ For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -16°C or above 54°C.		
AWOS-3 118.825	MEMPHIS CENTER 134.65 316.15	UNICOM 123.0 (CTAF)



2300 WASED		VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 21).		4 NM Holding Pattern	
1.5 NM to RW20		EDEPE 2200		016° → 14000 ← 196° 3000	
1.5 NM		3.5 NM		6.1 NM	
CATEGORY	A	B	C	D	
LPV DA	821-1		250 (300-1)		
LNAV/VNAV DA	917-1¼		346 (400-1¼)		
LNAV MDA	1060-1	489 (500-1)	1060-1½ 489 (500-1½)	1060-1½ 489 (500-1½)	
CIRCLING	1080-1	500 (500-1)	1300-2 720 (800-2)	1300-2¼ 720 (800-2¼)	