

|                                        |                        |                                                     |
|----------------------------------------|------------------------|-----------------------------------------------------|
| WAAS<br>CH <b>81909</b><br><b>W35A</b> | APP CRS<br><b>352°</b> | Rwy Ldg<br>TDZE <b>3176</b><br>Apt Elev <b>3188</b> |
|----------------------------------------|------------------------|-----------------------------------------------------|

RNAV (GPS) RWY 35

SHALZ FLD (CBK)

RNP APCH - GPS.

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -21°C or above 54°C. Baro-VNAV and VDP NA when using OEL altimeter setting. When local altimeter setting not received, use OEL altimeter setting and increase LPV DA to 3447 feet and all visibilities ¼ SM. Increase LNAV/VNAV DA to 3497 feet and all visibilities ¼ SM. Increase all MDAs 80 feet and LNAV visibility Cat C ¼ SM.

MISSED APPROACH: Climb to 5100 direct YEBVI and hold.

|                           |                                       |                                 |
|---------------------------|---------------------------------------|---------------------------------|
| AWOS-3P<br><b>118.175</b> | DENVER CENTER<br><b>132.7 226.675</b> | UNICOM<br><b>122.8 (CTAF) 0</b> |
|---------------------------|---------------------------------------|---------------------------------|

