

HI-ILS or LOC RWY 21

LOC/DME I-GTB 108.5 Chan 22	APCH CRS 209°	Rwy Idg 10,000 TDZE 677 Arpt Elev 690
---	-------------------------	--

[USA]

WHEELER-SACK AAF (KGTB)

DME or RADAR required.

- T** * When ALS inop, increase vis to $\frac{3}{4}$ mile.
 ** When ALS inop, increase CAT C vis to 1 mile,
 CAT DE vis to $1\frac{1}{4}$ miles.

ALSF-1





† MISSED APPROACH: Climb to 1200, then climbing right turn to 5000 direct ART VORTAC and hold. Continue climb in hold to 5000.

ATIS 119.525	APP CON 124.875 307.125	TOWER 118.75 290.25	GND CON 123.65 229.8	CLNC DEL 123.65	ASR/PAR
-----------------	----------------------------	------------------------	-------------------------	--------------------	---------

*** Circling NA E of Rwy 21 and 33.
Circling NA for CAT CD to Rwy 8.
Circling NA for CAT E to Rwy 8-26 and 15-33.


† ALTERNATE MISSED APPROACH: Or when directed by ATC, climb to 1200, then climbing right turn to 3000 via heading 250° within 10 NM. (RADAR required).

Use I-GTB DME
when on loc course.



A map showing the border between Canada and the United States. The border is marked with a dashed line. The word "CANADA" is written above the border, and "UNITED STATES" is written below the border.

EMERG SAFE ALT 100 NM 7600



CATEGORY	C	D	E
S-ILS 21*	877-1½	200	(200-½)
S-LOC 21**	1040-¾	363	(400-¾)
CIRCLING ***	1220-1½ 530 (600-1½)	1380-2¼ 690 (700-2¼)	1640-3 950 (1000-3)

ELEV 690 TDZE 677

Rwy 3 Idg 8637' 209°

Diagram showing runway layout, navigation aids (A1, A5, P, H, TWB), and distances (10,000 x 150, 4501 x 150, 5002 x 150, 0.5% UP). It also includes HIRL Rwy 3-21, 15-33, MIRL Rwy 8-26, and RAIL Rwy 15.

FAF to MAP 5.2 NM					
Knots	120	140	160	180	200
Min:Sec	2:36	2:14	1:57	1:44	1:34

FORT DRUM, NEW YORK

44°03'N-75°43'W

WHEELER-SACK AAF (KGTB)

Amdt 2 20APR23

HI-ILS or LOC RWY 21

NE-2, 25 DEC 2025 to 22 JAN 2026