

APP CRS

169°

Rwy Ldg

6930

TDZE

32

Apt Elev

34


RNAV (GPS) Y RWY 18

SPACE COAST RGNL (TIX)

DME/DME RNP-0.3 NA. Visibility reduction by helicopters NA.
When control tower closed, use Melbourne altimeter setting.
VDP NA when using Melbourne altimeter setting.

MISSED APPROACH: Climbing right turn to 1600 direct KYTEE and hold.

ATIS	ORLANDO APP CON	SPACE COAST TOWER ★	GND CON	UNICOM
120.625	134.95 281.425	118.9 (CTAF) 0	121.85	122.95



4 NM Holding Pattern

KYTEE

SAMPY

SHIRL 1.7 NM to STRUG

STRUG

1600

1600

1600

1600

319°

139°

139°

169°

2.88°

TCH 47

740

6 NM

2.8 NM

1 NM

0.7

0.5

ELEV 34

D TDZE 32

169°

81

7319 X 150

5000 X 100

27

36

TWR

CATEGORY	A	B	C	D
LNNAV MDA	440-1 408 (500-1)		440-1¼ 408 (500-1¼)	
CIRCLING	640-1 606 (700-1)		640-1¾ 606 (700-1¾)	640-2 606 (700-2)
MELBOURNE ALTIMETER SETTING MINIMUMS				
LNNAV MDA	500-1 468 (500-1)		500-1¼ 468 (500-1¼)	500-1½ 468 (500-1½)
CIRCLING	700-1 666 (700-1)		700-1¾ 666 (700-1¾)	700-2 666 (700-2)

MIRL Rwy 9-27

HIRL Rwy 18-36

REIL Rwys 9, 18, 27